



C/MRT SERIES

GEAR DRIVE TILLER

C/MRT models are intended for compact—midsize tractors. The CRT come with 4 blades per flange, the MRT model has 6 per, a Heavy Duty PTO shaft with slip-clutch for overload protection on both. The spring loaded tailgate smooths tilled ground for excellent seeding conditions. These tillers come in sizes of 4', 5', and 6'.



Model	Tillage Width	Drive	Type Of Blades	# of Blades	PTO Speed (rpm)	PTO Protection	Weight (lbs.)	Tractor Power (HP)
CRT-48	48"	Gear Drive	Type C	24	540	Slip Clutch	495	15-35
MRT-48	48"	Gear Drive	Type C	36	540	Slip Clutch	575	25-50
MRT-63	63"	Gear Drive	Type C	48	540	Slip Clutch	735	30-50
MRT-71	71"	Gear Drive	Type C	54	540	Slip Clutch	771	35-50

F SERIES

POLY HOPPER SPREADER



Accomplish all of your fertilizer spreading needs with ease with this three-point spreader. The poly hopper ensures you never have to worry about the hopper rusting. These spreaders come in two sizes to accommodate a variety of needs.

Model	Capacity (lbs.)	Capacity (Cu. Ft)	Hopper Height	Spread Swath	Weight (lbs.)
F300	860	10.6	42"	52'	120
F500	1,149	13.4	46"	52'	128

401 JEFFREYS ROAD
ROCKY MOUNT, NC 27804

www.cherokeeimplements.com



TEL: (252) 822-7140

FAX: (252) 787-5855

EMAIL: sales@cherokeeimplements.com



TC SERIES

CHAIN DRIVE TILLER

The TC series Rotary Tiller is rated for tractors up to 30 HP, the TC Series is a great tiller for small subcompact tractors. The TC has a heavy #80 drive chain and come in 3 working widths 40", 50" an 59" with 6 blades per flange and slip clutch protection.



Model	Description	Blades x Flange/PTO Protection	Drive	Weight (lbs.)
TC-40	40" Rotary Tiller	6 Blades / Slip Clutch	#80 Chain	337
TC-50	50" Rotary Tiller	6 Blades / Slip Clutch	#80 Chain	374
TC-59	59" Rotary Tiller	6 Blades / Slip Clutch	#80 Chain	412

RT SERIES

GEAR DRIVE TILLER



The RT is rated for compact tractors up to 60 HP. The heavy duty cast iron side with gear drive makes this tiller ideal for landscaping, gardening and hobby farms, nurseries, orchard operators, developers, and contractors. Available sizes are 4', 5', 6' and 7'. The RT comes standard with 6 blades per flange and slip clutch protection.

Model	Description	Blades x Flange/PTO Protection	Drive	Weight (lbs.)
RT4	4' Rotary Tiller	6 Blades / Slip Clutch	Gear	642
RT5	5' Rotary Tiller	6 Blades / Slip Clutch	Gear	732
RT6	6' Rotary Tiller	6 Blades / Slip Clutch	Gear	822
RT7	7' Rotary Tiller	6 Blades / Slip Clutch	Gear	1,023

** The weight and working data shown are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.